



# Product Sheet

DSM Food Specialties B.V.

P.O. Box 1  
2600 MA Delft  
The Netherlands

[www.dsm.com](http://www.dsm.com)

## Delvotest<sup>®</sup> Incubator

Description	The Delvotest <sup>®</sup> dry incubator with integrated thermometer and timer functions has been developed for incubating the antibiotic residue test ampoule presentations of Delvotest <sup>®</sup> . It is a ready-to-use electronic heating device with a thermostatically controlled temperature, which meets the required specifications for optimal performance of Delvotest ampoules.
Presentation	A plastic casing with an internal metal incubating block for positioning 10 Delvotest <sup>®</sup> ampoules. The dry incubator has a digital thermometer and timer functions programmable to customer needs. The device comes with a Continental European CEE VIIG* plug. (* Some countries may have other plugs appropriate for local use). A 12 Vdc version with a cigarette lighter plug and a 24 Vdc truck version are available on request. Verify country regulations on use of accessories while driving.
Specifications	<p>Thermometer and timer settings:</p> <ul style="list-style-type: none"> <li>- Temperature setting : 64°C</li> <li>- Fine adjustment : +/- 1°C</li> <li>- Temperature accuracy : +/- 0.2°C</li> <li>- Operating temperature : +10 to +35°C (ambient)</li> </ul> <p>UL-rating specifications on usage:</p> <ul style="list-style-type: none"> <li>- Indoor use only</li> <li>- Maximum altitude : 2000 meter</li> <li>- Maximum relative humidity : 80% at 31°C</li> <li>- Transition surge level II</li> <li>- Pollution degree level 2</li> </ul> <p>Timer settings:</p> <ul style="list-style-type: none"> <li>- Alarm sound or electronic switch-off setting</li> <li>- Time set programmable (hour/min.): 1:45, 2:00, 2:15, 2:30, 2:45, 3:00 and 3:15</li> <li>- Timer accuracy : &lt;2.7%</li> </ul>
Technical data	<p>Power supply : 115* / 230 Vac +/-10%. (* USA use: power cords maximum 125 Vac)</p> <p>Frequency : 50/60 Hz.</p> <p>Power consumption : 20 W</p> <p>Main fuses SMD 2 x 315mA F</p> <p>Weight : 0.5 Kg</p>
Certification	EN61010-1 /A1/A2
CE-conformity	EN61326-1
UL-rating	EN55022 EN61000-4 /-2 /-3 /-4 /-5 /-6 /-11 UL61010-1 (E219101 Listed:1GD4)
Guarantee	The product is guaranteed to be free from defective materials and workmanship provided that misuse, alteration and/or abnormal use have not occurred. Do not open or repair defective incubators but contact DSM representative. It will be repaired under warranty for a period of 2 years from the date of manufacture printed on the bottom of the incubator casing. Products NOT repaired by DSM (third party repair) are excluded from guarantees.

Although diligent care has been used to ensure that the information provided herein is accurate, nothing contained herein can be construed to imply any representation or warranty for which we assume legal responsibility, including without limitation any warranties as to the accuracy, currency or completeness of this information or of non-infringement of third party intellectual property rights. The content of this document is subject to change without further notice. Please contact us for the latest version of this document or for further information. Since the user's product formulations, specific use applications and conditions of use are beyond our control, we make no warranty or representation regarding the results which may be obtained by the user. It shall be the responsibility of the user to determine the suitability of our products for the user's specific purposes and the legal status for the user's intended use of our products.

DSM Food Specialties B.V. | A. Fleminglaan 1 | 2613 AX Delft | The Netherlands | [info.food@dsm.com](mailto:info.food@dsm.com) | Trade Register Number 27235314